Three Phase Industrial Male Plug

INGRESS PROTECTION

IP66

Approval numbers and compliance certificates for this range are available on request — contact us.

RATED VOLTAGE

500 V AC

RATED FREQUENCY

50 / 60 Hz

DIMENSIONS

Ø78 mm; straight 169–201 mm, angled 182 mm / 94 mm offset

YELE®

Three Phase Industrial Male Plug

Features:

- Approval No.: SAA151879
- Standard: AS/NZS3123
- Rated Voltage:500V AC
- Rated Frequency:50/60Hz
- IP Protection:IP66

Cat. No.	Description	Rating (Amp)	Voltage (V)	No.of Phase
AB66P410	4 Pins Straight Male Plug	10	500	3
AB66P420	4 Pins Straight Male Plug	20	500	3
AB66P432	4 Pins Straight Male Plug	32	500	3
AB66P440	4 Pins Straight Male Plug	40	500	3
AB66P450	4 Pins Straight Male Plug	50	500	3
AB66P510	5 Pins Straight Male Plug	10	500	3
AB66P520	5 Pins Straight Male Plug	20	500	3
AB66P532	5 Pins Straight Male Plug	32	500	3
AB66P540	5 Pins Straight Male Plug	40	500	3
AB66P550	5 Pins Straight Male Plug	50	500	3
AB66PA410	4 Pins Angled Male Plug	10	500	3
AB66PA420	4 Pins Angled Male Plug	20	500	3
AB66PA432	4 Pins Angled Male Plug	32	500	3
AB66PA440	4 Pins Angled Male Plug	40	500	3
AB66PA450	4 Pins Angled Male Plug	50	500	3
AB66PA510	5 Pins Angled Male Plug	10	500	3
AB66PA520	5 Pins Angled Male Plug	20	500	3
AB66PA532	5 Pins Angled Male Plug	32	500	3
AB66PA540	5 Pins Angled Male Plug	40	500	3
AB66PA550	5 Pins Angled Male Plug	50	500	3

Dimensions(mm)

Page / 12

Dimensions and product views